


# EasyLog 5 Development Plan

1 July 2005



(c) 2005 Microware Software - Italy

This document contains confidential information that can not be distributed without the prior permission of Microware Software snc.

# List of developments for 5.1.0.14

## EasyLog 5 main module

---

### Automatic determination of UTC difference

The UTC difference with your local date time is now detected from the Windows environment. This will also automatize the adjustment from and to daylight.

### PSK Window

Text colors of the communication windows can be now freely selected by the user.

### DX-List

All the spot of the DX-List are now saved to disk and reloaded the next time you will run the program. A new button in the toolbar of the DX-List window allows to switch on and off this feature. By default auto save of the incoming DX-Spot is enabled.

### Regional setting dialog box

This window groups the most important regional settings used by EasyLog and the other modules. This window pop-up automatically at the first run of EasyLog but can also be opened at any time by a new option of the Log menu.

### Language localization

The identification and fixing of the language resources still not translated around the program is going on. Several new language resources have been found and added to the language files.

### Language selection dialog box

After changing language by EasyLog 5 main module, it didn't appear anymore the information dialog box informing the user that EasyLog must be restarted to apply the language change.

### WPX tracking

Changes in the WPX tracking algorithm, fixed some problems recompiling the award if prefixes were credited.

### 4 characters long Locators & DX-Map

4 character long locators are now plotted correctly in the DX Map

### DX-Map used wrong locator to identify the DX-Wrong locator

Under some circumstances the DX-country was located by using a wrong reference locator

### Wrong identifiers on user function buttons in PSK window

The 7<sup>th</sup> button was erroneously labeled as F9

---

## **Path between home QTH and DX locator**

---

The path between home locator and DX Locator was not showed the first time DX Map was opened.

## **UTC Error**

Fixed bug of automatic UTC determination (bug introduced with beta 5.1.0.3)

## **Tasto Tune finestra PSK**

---

Il tasto attivava il Tune ma non lo disattivava ad un secondo click

## **Error esporting e-QSL**

There was an error on date field exporting e-QSL to ADIF file when ANSI date format was selected Tnx to SM5YY and Scandinavian users

## **Search and Print on ASCII file – error when “save as”**

Printing on ASCII file from Search and Print section, and then selecting “Save As” from Notepad, an error 0x3200 was generated

## **Time fields format loss**

Due to external events (as for example deleting the cache on the MS Internet Explorer) EasyLog forgot the time format. The seconds appeared on the time panel and even in the Add QSO window (F2) Tnx I4HRH e IH9GPI

## **Error in populating Band / RST and Mode fields**

If the 'Read Frequency from Radio' setting was checked, opening the Log entry window the frequency was read and the Band, RST and Mode fields populated automatically. If the Log entry window was closed by using the [x] or the Close button the next time the log entry window was opened the frequency was read but the Band, RST and Mode fields were not populated anymore.

*Tnx to the reporters of this bug: Michel HB9REZ, and Tim W4TME for the detailed description that was a big help to reproduce this bug.*

## **4 character Locators were ignored in DXMap**

If a QSO with a 4 character long locator was logged, opening the DXMap you could not see the path on the map. 4 characters locators were ignored.

*Tnx to Carlo I4HRH for insisting reporting the persistence of this bug.*

## **Error calculating a Locator from coordinates**

In The QRB dialog box (visible by clicking the QRB button in the Antenna panel) locators calculated by coordinates were wrong, the last two characters of the locator were always 'AA'

*Tnx to Bengt SM5YY for the report of this bug*

## **QSL Wizard – 5.0.0.10**

---

### **Printing with Offset**

If QSL buffer contained only 1 record, printing by using label offset didn't work, an empty preview was showed.

### **Custom format**

Custom format (introduced with 5.0.0.7) was not saved to file.

## **Print Award – 5.0.0.12**

---

### **Default page format**

Print Award now reads the same default page format configured in the regional setting dialog box.

Crash selecting WPX award

## **Printer Log – 5.0.0.12**

---

### **Formato pagina di default**

Printer Log now reads the same default page format configured in the regional setting dialog box.

## **WINCE**

---

### **New EasyLog5 for WINCE**

The Callsign field was not imported during synchronization with EasyLog5. The new exe file is available in the U.R.A.